


BDT

M2080 Military Binocular Series

STEINER 



M2080 Military Binocular, shown in green



Standard Military Reticle

Lines, numbers and indicators are designed to be easily readable in daylight as well as in artificial light. The reticle is adjusted parallax free to infinity and is built into the right half of the binocular.

For visual efficiency, extended-viewing comfort and object detail, traditional spotting scopes can't compare to these high power military binoculars. Originally developed for perimeter and border patrol applications, they now serve military and law enforcement agencies around the world. The massive 80mm objective lenses and unmatched Steiner quality deliver far superior low-light performance and image acuity for artillery teams, SEAL missions, surveillance missions, air traffic controllers, forest fighters and naval patrols.

Available with or without a reticle.

All the features of the 15x80 with even higher magnification for greater range without sacrificing the field of view. Excellent for border observation, airports and airspace monitoring.



M2080 Military Binocular Series Features



Global Item Number
2675
US Product Code / SKU
840229102198

M2080



Global Item Number
2676
US Product Code / SKU
840229102204

Special Features
Standard Military Reticle

M2080r

Magnification 20x	Pressure Resistance 0.5 bar
Focus System Sports-Auto-Focus™	Resolving Power ± 3"
Optics Systems Fully multi-coated	Dioptric Range ± 5 dpt
Close Focus 60 m (197 ft.)	Field of View 92 m (301 ft.)
Entrance Pupil 80 mm	Field of View @ 1,000 m ≥ 48 m
Exit Pupil 5.3 mm	Field of View Angular 2.75°
Luminosity 28	Eye Relief 16 mm
Twilight Factor 34.6	Weight for Ocular Accessories (approx.) Carrying Strap: 55 g (1.9 oz.) Objective Caps: 52 g (1.8 oz.) Eyepiece Cover: 18 g (0.6 oz.)
Eyecups Cylindrical	Neck Strap Standard
Rubbing Armoring NBR Long Life	Neck Strap Attachment Standard
Waterproof Submersion to 5 m (16 ft.)	Objective Cover Yes
Weight 1,930 g (68 oz.)	Rain Protection Cap Yes
Interpupillary Distance 56 - 74 mm	Special Features Tripod mount, Military specifications
Temperature Range -40°C to +80°C (-40°F to +176°F)	

Applications: Standard issue Binocular for

- Military
- Law Enforcement

*Specifications subject to change without notice.
Figures correspond to an ocular adjustment to 0 dpt. and an ID of 65 mm.



For International Defense and Military Sales of Binoculars and Riflescopes:

STEINER-OPTIK GmbH
Defense & Law Enforcement Division
Dr.-Hans-Frisch-Str. 9
D-95448 Bayreuth
Germany

Tel: +49 921 7879-0
Fax: +49 921 7879-88
Email: military@steiner.de

For US Law Enforcement and US Military Sales, all Steiner Optics and eOptics products:

Steiner-Optics
331 East 8th Street
Greeley, CO 80631
United States

Tel: (970) 356-1670
Toll free (888) 228-7747
Fax: (970) 356-8702
Email: MilitarySales@steiner-optics.com
LESales@steiner-optics.com

For International Law Enforcement and Military Sales of eOptics products:

Steiner-eOptics®
70 Garden Court
Monterey, CA 93940
United States

Tel: +1 831-373-0701
Fax: +1 831-373-0903
Email: sales@steiner-eoptics.com

For all Military and Law Enforcement Sales of Steiner STS products (formerly The O'Gara Group Sensor Systems, STS and Diffraction LTD):

Steiner-STS
2794 Indian Ripple Road
Beavercreek, OH 45440
United States

Tel: (937) 426-2341
Fax: (937) 426-4820
Email: sales@steiner-STS.com



BerettaDefenseTechnologies.com