

**1BDT**

# M5Xi Military 1-5x24 Rifle Scope

**STEINER** 



M5Xi Military 1-5x24 Rifle Scope



The German-made M5Xi series features world-class engineering and optical systems, built to strict military specs and precisely crafted for victory—on the battlefield, or in competition. The 1-5x is for marksmen rifles, patrol rifles and AR/M4 platforms, with true eyes-open 1x magnification, and 5x zoom to locate targets at longer distances.

Close-combat scope with 30 mm tube, Rapid Dot reticle calibrated in either 5.56 or 7.62, true 1x eyes open capability for situational awareness and 5x power to engage distant targets.



Rapid Dot 5.56 Reticle



Rapid Dot 7.62 Reticle



# M5Xi Military 1-5x24 Rifle Scope Features



## 1-5x24

**Global Product Code / SKU**

8706 094 308

**Global Item Number**

8706-5.56

**Global Turret Spin Direction**

Clockwise

**US Product Code / SKU**

000381855718

**US Item Number**

5571

**US Turret Spin Direction**

Counter clockwise

**Reticle**

Rapid Dot 5.56



## 1-5x24

**Global Product Code / SKU**

8706 094 303

**Global Item Number**

8706-7.62

**Global Turret Spin Direction**

Clockwise

**US Product Code / SKU**

000381855701

**US Item Number**

5570

**US Turret Spin Direction**

Counter clockwise

**Reticle**

Rapid Dot 7.62

*Specifications subject to change without notice.*

<b>Magnification</b> 1-5x	<b>Wind/Elevation Click Value</b> 1 cm (0.1 mrad)
<b>Objective Lens</b> 24 mm	<b>Windage Range at 100 m.</b> +/- 160 cm (16 mils)
<b>Focal Plane</b> 2nd	<b>Elevation Range at 100.</b> 320 cm (32 mils)
<b>Focal Plane Location</b> Front	<b>Parallax/Focus</b> Fixed
<b>Tube Diameter</b> 30 mm (3.0 cm)	<b>Parallax/Focus Range</b> 100 m (328 ft.)
<b>Field of View at 109 yds (100 m)</b> 36 - 7.2 m (118.1 - 23.7 ft.)	<b>Rubber Armoring</b> Yes
<b>Eye Relief</b> 88.9 - 109.2 mm (8.9 - 10.9 cm)	<b>Storage Temperature Range</b> -35°C to +70°C (-31°F to +158°F)
<b>Exit Pupil</b> 7.0 - 4.8 mm (.7 - .48 cm)	<b>Operating Temperature Range</b> -25°C to 63°C (-13°F to +145°F)
<b>Twilight Factor</b> 2.65 - 10.95	<b>Lens Cap</b> Yes
<b>Length</b> 294.6 mm (11.6 in.)	<b>Waterproof/Fogproof</b> Submersible to 10 m (33 ft.)
<b>Weight</b> With caps - 585 g (1.3 lbs) Without caps - 555 g (1.2 lbs)	<b>Nitrogen Filled</b> Yes
<b>Diopter Adjustment Range</b> +2 to -3	<b>Battery</b> CR 2450
<b>Illumination Control</b> Rotary digital control, turret mounted with 11 illumination settings (7 night & 4 day), 2 off settings, and 10 standby (light-off) settings	<b>Special Features</b> Adjustable knobs 100% sealed
<b>Elevation Adjustment Knob</b> Resettable to Zero with wrench Visual & tactile indication of turns	<b>Color</b> Black

### Applications: Standard issue Rifle Scope for

- Military
- Law Enforcement



**For International Defense and Military Sales of Binoculars and Riflescopes:**

STEINER-OPTIK GmbH  
Defense & Law Enforcement Division  
Dr.-Hans-Frisch-Str. 9  
D-95448 Bayreuth  
Germany

Tel: +49 921 7879-0  
Fax: +49 921 7879-88  
Email: military@steiner.de

**For US Law Enforcement and US Military Sales, all Steiner Optics and eOptics products:**

Steiner-Optics  
331 East 8th Street  
Greeley, CO 80631  
United States

Tel: (970) 356-1670  
Toll free (888) 228-7747  
Fax: (970) 356-8702  
Email: MilitarySales@steiner-optics.com  
LESales@steiner-optics.com

**For International Law Enforcement and Military Sales of eOptics products:**

Steiner-eOptics®  
70 Garden Court  
Monterey, CA 93940  
United States

Tel: +1 831-373-0701  
Fax: +1 831-373-0903  
Email: sales@steiner-eoptics.com

**For all Military and Law Enforcement Sales of Steiner STS products (formerly The O'Gara Group Sensor Systems, STS and Diffraction LTD):**

Steiner-STS  
2794 Indian Ripple Road  
Beavercreek, OH 45440  
United States

Tel: (937) 426-2341  
Fax: (937) 426-4820  
Email: sales@steiner-STS.com



BerettaDefenseTechnologies.com