


M750 Military Binocular Series



M750rc, M750r, M750rc LPF – Gen II



HD Stabilized Liquid Dampened Compass
 360° rose, 1° graduation (6.400 mils rose, 20 mils graduation)
 Compass exactness $\pm 0.5^\circ$
 Angle of inclination $\pm 7^\circ$



Military Ranging Reticle
 Lines, numbers and indicators are designed to be easily readable in daylight as well as in artificial light

When tactical operations take place in challenging conditions – and they always do – these are the optics to count on. Proven on missions from extreme darkness to high-altitude sun, arctic cold to desert heat, they give you exactly the optical capabilities you need: mid-90% light transmission, image clarity from edge to edge, belly crawling toughness, even integrated compass, range-finding or custom reticles, and laser protection if desired. When your mission demands optical superiority, now you have it.

All models feature an integrated reticle that can be used to judge both the height and distance to a target.

Some models feature an integrated compass giving you the ability to accurately identify targets and determine bearings and distance to the single degree.

Available with either Generation II or Generation III LPF (Laser Protection Filters) to authorized buyers. Please contact us for details.

Offers exceptionally bright images in all light conditions, especially useful for nighttime ops. Crisp resolution and a wide field of view help you locate and identify targets faster and more accurately.



M750r Military Binocular Series Features



Global Item Number
2650

US Product Code / SKU
840229102105

Dimensions (approx.)*
140 x 205.7 x 76.2 mm
(5.5 x 8.10 x 3.0 in.)

Special Features
Mil Ranging Reticle,
Military Specifications

M750r



Global Item Number
2651

US Product Code / SKU
840229102112

Laser Protection Filter
Laser protection against any laser starting at 800 nm up to max. 1,600 nm (broad band protection)

Dimensions (approx.)*
140 x 205.7 x 76.2 mm
(5.5 x 8.10 x 3.0 in.)

Special Features
Mil Ranging Reticle,
Military Specifications

M750r LPF – Gen II



Global Item Number
2652

US Product Code / SKU
840229102129

Laser Protection Filter
Broad band laser protection from 800 – 1,600 nm plus extra protection at 532 nm (green laser)

Dimensions (approx.)*
140 x 205.7 x 76.2 mm
(5.5 x 8.10 x 3.0 in.)

Special Features
Mil Ranging Reticle,
Military Specifications

M750r LPF – Gen III

Magnification
7x

Weight
1,125 g (39.7 oz.)

Focus System
Sports-Auto-Focus™

Optics Systems
Fully multi-coated

Close Focus
20 m (66 ft.)

Entrance Pupil
50 mm

Exit Pupil
7.14 mm

Luminosity
51

Twilight Factor
18.7

Eyecups
Cylindrical

Rubbering Armoring
NBR Long Life

Waterproof
Submersion to 5 m (16 ft.)

Interpupillary Distance
56 - 74 mm

Temperature Range
-40°C to +80°C
(-40°F to +176°F)

Pressure Resistance
0.5 bar

Resolving Power
≥ 8.6"

Dioptic Range
± 5 dpt

Field of View @ 1,000 m
≥ 130 m

Field of View Angular
7.4°

Weight for Ocular Accessories (approx.)
Carrying Strap: 55 g (1.9 oz.)
Objective Caps: 42 g (1.5 oz.)
Eyepiece Cover: 18 g (0.6 oz.)

Neck Strap
Standard

Neck Strap Attachment
Standard

Objective Cover
Yes

Rain Protection Cap
Yes

Applications: Standard issue Binocular for

- Military
- Law Enforcement

Specifications subject to change without notice.

**Figures correspond to an ocular adjustment to 0 dpt. and an ID of 65 mm.*



For International Defense and Military Sales of Binoculars and Riflescopes:

STEINER-OPTIK GmbH
Defense & Law Enforcement Division
Dr.-Hans-Frisch-Str. 9
D-95448 Bayreuth
Germany

Tel: +49 921 7879-0
Fax: +49 921 7879-88
Email: military@steiner.de

For US Law Enforcement and US Military Sales, all Steiner Optics and eOptics products:

Steiner-Optics
331 East 8th Street
Greeley, CO 80631
United States

Tel: (970) 356-1670
Toll free (888) 228-7747
Fax: (970) 356-8702
Email: MilitarySales@steiner-optics.com
LESales@steiner-optics.com

For International Law Enforcement and Military Sales of eOptics products:

Steiner-eOptics®
70 Garden Court
Monterey, CA 93940
United States

Tel: +1 831-373-0701
Fax: +1 831-373-0903
Email: sales@steiner-eoptics.com

For all Military and Law Enforcement Sales of Steiner STS products (formerly The O'Gara Group Sensor Systems, STS and Diffraction LTD):

Steiner-STS
2794 Indian Ripple Road
Beavercreek, OH 45440
United States

Tel: (937) 426-2341
Fax: (937) 426-4820
Email: sales@steiner-STS.com



BerettaDefenseTechnologies.com

M750rc Military Binocular Series Features



Global Item Number
2690
US Product Code / SKU
840229102259

Dimensions (approx.)*
140 x 207 x 95 mm
(5.5 x 8.15 x 3.7 in.)
Special Features
HD Stabilized Compass,
Mil Ranging Reticle,
Military Specifications

Magnification
7x

Temperature Range
-40°C to +80°C
(-40°F to +176°F)

Weight
1,125 g (39.7 oz.)

Pressure Resistance
0.5 bar

Focus System
Sports-Auto-Focus™

Resolving Power
≥ 7.5"

Optics Systems
Fully multi-coated

Dioptic Range
± 5 dpt

Close Focus
20 m (66 ft.)

Field of View @ 1,000 m
≥ 130 m

Entrance Pupil
50 mm

Field of View Angular
7.4°

Exit Pupil
7.14 mm

Weight for Ocular Accessories (approx.)
Carrying Strap: 55 g (1.9 oz.)
Objective Caps: 42 g (1.5 oz.)
Eyepiece Cover: 18 g (0.6 oz.)

Luminosity
51

Twilight Factor
18.7

Eyecups
Cylindrical

Neck Strap
Standard

Rubbering Armoring
NBR Long Life

Neck Strap Attachment
Standard

Waterproof
Submersion to 5 m (16 ft.)

Objective Cover
Yes

Interpupillary Distance
56 - 74 mm

Rain Protection Cap
Yes

Battery
1.5V 350

M750rc



Global Item Number
2691
US Product Code / SKU
840229102266

Dimensions (approx.)*
140 x 207 x 95 mm
(5.5 x 8.15 x 3.7 in.)
Special Features
HD Stabilized Compass,
Mil Ranging Reticle,
Military Specifications

Compass
HD Stabilized Compass

Laser Protection Filter
Laser protection against any laser starting at 800 nm up to max. 1,600 nm (broad band protection)

Eyecups
Cylindrical

Neck Strap
Standard

Rubbering Armoring
NBR Long Life

Neck Strap Attachment
Standard

Waterproof
Submersion to 5 m (16 ft.)

Objective Cover
Yes

Interpupillary Distance
56 - 74 mm

Rain Protection Cap
Yes

Battery
1.5V 350

M750rc LPF – Gen II



Global Item Number
2692
US Product Code / SKU
840229102273

Dimensions (approx.)*
140 x 207 x 95 mm
(5.5 x 8.15 x 3.7 in.)
Special Features
HD Stabilized Compass,
Mil Ranging Reticle,
Military Specifications

Compass
HD Stabilized Compass

Laser Protection Filter
Broad band laser protection from 800 – 1,600 nm plus extra protection at 532 nm (green laser)

Eyecups
Cylindrical

Neck Strap
Standard

Rubbering Armoring
NBR Long Life

Neck Strap Attachment
Standard

Waterproof
Submersion to 5 m (16 ft.)

Objective Cover
Yes

Interpupillary Distance
56 - 74 mm

Rain Protection Cap
Yes

Battery
1.5V 350

M750rc LPF – Gen III

Specifications subject to change without notice.

**Figures correspond to an ocular adjustment to 0 dpt. and an ID of 65 mm.*

Applications: Standard issue Binocular for

- Military
- Law Enforcement



For International Defense and Military Sales of Binoculars and Riflescopes:

STEINER-OPTIK GmbH
Defense & Law Enforcement Division
Dr.-Hans-Frisch-Str. 9
D-95448 Bayreuth
Germany

Tel: +49 921 7879-0
Fax: +49 921 7879-88
Email: military@steiner.de

For US Law Enforcement and US Military Sales, all Steiner Optics and eOptics products:

Steiner-Optics
331 East 8th Street
Greeley, CO 80631
United States

Tel: (970) 356-1670
Toll free (888) 228-7747
Fax: (970) 356-8702
Email: MilitarySales@steiner-optics.com
LESales@steiner-optics.com

For International Law Enforcement and Military Sales of eOptics products:

Steiner-eOptics®
70 Garden Court
Monterey, CA 93940
United States

Tel: +1 831-373-0701
Fax: +1 831-373-0903
Email: sales@steiner-eoptics.com

For all Military and Law Enforcement Sales of Steiner STS products (formerly The O'Gara Group Sensor Systems, STS and Diffraction LTD):

Steiner-STS
2794 Indian Ripple Road
Beavercreek, OH 45440
United States

Tel: (937) 426-2341
Fax: (937) 426-4820
Email: sales@steiner-sts.com



BerettaDefenseTechnologies.com